



By **BEEESWIFT**



Specialized Workwear

Safety and Protection

ARC COMPLIANT BALACLAVA

- Flame Retardant, Anti-Static, ARC Flash Balaclava hood.
- 210gsm 60/40 Modacrylic/ cotton with anti static.
- Inherently flame retardant fabric.
- FR properties will not diminish with repeated laundering
- Soft comfortable fabric with contrast FR sewing thread

EN ISO 13688: 2013
EN 1149-3: 2008
EN 1149-5: 2015
EN ISO 11612: 2015 (A1 B1 C1)
EN ISO 14116: 2015 (3/5H/40)

IEC 61482-2-2009
EN 61482-1-2-2007 (Class 1 = 4 kA) - Box Arc testing
EN 61482 - 1 - 1 : 2009 (EBT50 = 5.9 cAL/cm2) Open Arc testing

- Each garment style is independantly tested to both box and open ARC standards.
- Click ARC production is covered by article 11B certification.



ARC FLASH GO/RT COVERALL

- Fire Retardant, Hi Vis, Anti-static, ARC Flash Orange Coverall.
- GO/RT 3279 issue 8 2013 for use on or around railway lines.
- 310gsm 40% Modacrylic 24% Viscose, 20% Polyester, 10% Cotton, 4% Aramid, 2% Anti-static Fibre.
- 2 hip pockets.
- Large bellows pocket to each leg with Velcro closure flap.
- Right leg mobile phone pocket with Velcro closure flap.
- All pocket flaps with Retro-reflective tape feature.
- Internal knee pad pouches.
- Large qualifying icons on left leg pocket.
- Adjustable leg bellows.

- EN ISO 13688:2013 - General requirements for protective clothing
- EN ISO 20471:2013 Class 3 - Test method for high visibility - GORT 3279 Issue 8
- EN 1149-3:2004 - Anti Static - Test methods for measurements of charge decay
- EN 1149-5:2008 - Anti Static - Material performance and design requirements
- EN ISO 11611:2015 (Class 1 A1 A2) - Protective clothing for use in welding
- EN ISO 11612:2015 (A1 A2 B1 C1) - Protection against heat and flame

ARC FLASH

IEC 61482-2:2009 - Performance requirements and design requirements
EN 61482-1-2:2007 (Class 1 = 4kA) - Box Arc testing
EN 61482-1-1:2009 (ATPV = 16 Cal/cm2) - Open Arc testing

- Each garment style is independantly tested to both box and open ARC standards.
- Click ARC production is covered by article 11B certification.



Product Code:
CARC28

Available in Colours:



As Shown



Product Code:
CARC53OR

Available in Sizes:
38 - 56 (Tall Leg Available)

Available in Colours:



Orange
CARC53OR



Anti Static



ARC Flash Protection



Fire Retardant



Hi Visibility



Protection for Welding and
Allied Processes

ARC FLASH COVERALL

- Fire retardant, Anti-static, ARC Flash coverall.
- 300gsm 60/40 Modacrylic/cotton blend.
- Triple stitch construction.
- 2 hip pockets.
- Rear patch pocket with Velcro closure flap.
- Large bellows pocket to each leg with Velcro closure flap.
- Right leg mobile phone pocket with Velcro closure flap.
- All pocket flaps with Retro-reflective tape feature.
- Internal knee pad pouches.
- Large qualifying icons on left leg pocket.

EN ISO 13688:2013 - General requirements for protective clothing
EN 1149-3:2004 - Anti Static - Test methods for measurements of charge decay
EN 1149-5:2008 - Anti Static - Material performance and design requirements
EN ISO 11611:2007 (Class 1 A1 A2) - Protective clothing for use in welding
EN ISO 11612:2008 (A1 A2 B1 C1) - Protection against heat and flame

ARC FLASH

IEC 61482-2:2009 - Performance requirements and design requirements
EN 61482-1-2:2007 (Class 1 = 4kA) - Box Arc testing
EN 61482-1-1:2009 (ATPV = 10.8 Cal/cm2) - Open Arc testing

- Each garment style is independantly tested to both box and open ARC standards.
- Click ARC production is covered by article 11B certification.



ARC FLASH COVERALL TWO TONE

- Fire Retardant, Hi Vis, Anti-static, ARC Flash two tone coverall.
- 300gsm 60/40 Modacrylic/cotton blend.
- Triple stitch construction.
- 2 hip pockets.
- Large bellows pocket to each leg with Velcro closure flap.
- Right leg mobile phone pocket with Velcro closure flap.
- All pocket flaps with Retro-reflective tape feature.
- Internal knee pad pouches.
- Large qualifying icons on left leg pocket.

EN ISO 13688:2013 - General requirements for protective clothing
EN ISO 20471:2013 Class 3 - Test method for high visibility
EN 1149-3:2004 - Anti Static - Test methods for measurements of charge decay
EN 1149-5:2008 - Anti Static - Material performance and design requirements
EN ISO 11611:2015 (Class 1 A1 A2) - Protective clothing for use in welding
EN ISO 11612:2015 (A1 A2 B1 C1) - Protection against heat and flame

ARC FLASH

IEC 61482-2:2009 - Performance requirements and design requirements
EN 61482-1-2:2007 (Class 1 = 4kA) - Box Arc testing
EN 61482-1-1:2009 (ATPV = 10.8 Cal/cm2) - Open Arc testing

- Each garment style is independantly tested to both box and open ARC standards.
- Click ARC production is covered by article 11B certification.



ARC FLASH POLO SHIRT

- Flame Retardant, Anti-Static, ARC long sleeved polo shirt.
- 210gsm 60/40 Modacrylic/cotton blend Pique fabric.
- Inherently flame retardant fabric.
- FR properties will not diminish with repeated laundering.
- For industrial workers exposed to heat.
- Not suitable for fire fighters.
- 3 Button placket.
- Ribbed cuffs.
- Robust yet soft and comfortable to wear.

EN ISO 13688:2013 - General requirements for protective clothing
 EN 1149-3:2004 - Anti Static - Test methods for measurements of charge decay
 EN 1149-5:2008 - Anti Static - Material performance and design requirements
 EN ISO 11612:2015 (A1 A2 B1 C1) - Protection against heat and flame

ARC FLASH

IEC 61482-2:2009 - Performance requirements and design requirements
 EN 61482-1-2:2007 (Class 1 = 4kA) - Box Arc testing
 EN 61482-1-1:2009 (EBT50 = 5.0 Cal/cm2) - Open Arc testing

- Each garment style is independantly tested to both box and open ARC standards.
- Click ARC production is covered by article 11B certification.



ARC FLASH HI VIZ POLO SHIRT

- Fire Retardant, Hi-Vis, Anti-Static, ARC Flash long sleeved polo shirt.
- 280gsm 60/40 Modacrylic/cotton blend PDR fabric.
- Inherently flame retardant.
- Fire Retardant properties will not diminish with repeated laundering.
- For industrial workers exposed to heat.
- Not suitable for fire fighters.
- 3 Button placket.
- Ribbed cuffs.
- Very robust yet soft and comfortable to wear.

EN ISO 13688:2013 - General requirements for protective clothing
 EN ISO 11612:2015 (A1 A2 B1 C1)
 EN ISO 20471:2013 (CLASS 3)
 EN 1149-3:2004 - Anti Static - Test methods for performance of charge decay
 EN 1149-5:2008 - Anti Static - Protection against heat and flame

ARC FLASH

IEC 61482-2:2009 - Performance requirements and design requirements
 EN 61482-1-1:2009 (ATPV = 9.1 Cal/cm2) - Open Arc testing
 EN61482-1-2:2007 (CLASS 1 = 4kA) - Box Arc testing

- Each garment style is independantly tested to both box and open ARC standards.
- Click ARC production is covered by article 11B certification.



Product Code:
CARC1

Available in Sizes:
S - 6XL

Available in Colours:



Navy Blue
CARC1N



Anti Static



Arc Flash Protection



Fire Retardant



Product Code:
CARC2

Available in Sizes:
S - 6XL

Available in Colours:



Saturn Yellow
CARC2HVS



Anti Static



Arc Flash Protection



Fire Retardant



Hi Visibility

ARC FLASH GO/RT POLO SHIRT

- Fire Retardant, Hi-Vis, Anti-Static, ARC Flash long sleeved polo shirt.
- GO/RT 3279 issue 8 2013 for use on or around railway lines.
- 220gsm 66% Modacrylic, 32% Polyester, 2% Carbon.
- Inherently flame retardant.
- Fire Retardant properties will not diminish with repeated laundering.
- For industrial workers exposed to heat.
- Not suitable for fire fighters.
- 3 Button placket.
- Ribbed cuffs.
- Very robust yet soft and comfortable to wear.

EN ISO 13688:2013 - General requirements for protective clothing
EN ISO 11612:2015 (A1 B1 C1)
EN ISO 20471:2013 (CLASS 3) - GORT 3279 2013 Issue 8
EN 1149-3:2004 - Anti Static - Test methods for performance of charge decay
EN 1149-5:2008 - Anti Static - Protection against heat and flame

ARC FLASH
IEC 61482-2:2009 - Performance requirements and design requirements
EN 61482-1-1:2009 (ATPV = 6.2 Cal/cm²) - Open Arc testing
EN 61482-1-2:2007 (CLASS 1 = 4kA) - Box Arc testing

- Each garment style is independantly tested to both box and open ARC standards.
- Click ARC production is covered by article 11B certification.



ARC FLASH SWEATSHIRT

- Fire Retardant, Anti-Static, ARC Flash sweatshirt.
- 300gsm 60/40 Modacrylic/Cotton blend fabric.
- Inherently flame retardant.
- Fire Retardant properties will not diminish with repeated laundering.
- Ribbed cuffs.
- Ribbed waistband.
- For industrial workers exposed to heat.
- Not suitable for fire fighters.

EN ISO 13688:2013 - General requirements for protective clothing
EN 1149-3:2004 - Anti Static - Test methods for measurements of charge decay
EN 1149-5:2008 - Anti Static - Material performance and design requirements
EN ISO 11612:2015 (A1 B1 C2) - Protection against heat and flame

ARC FLASH
IEC 61482-2:2009 - Performance requirements and design requirements
EN 61482-1-2:2007 (Class 1 = 4kA) - Box Arc testing
EN 61482-1-1:2009 (ATPV = 12.6 Cal/cm²) - Open Arc testing

- Each garment style is independantly tested to both box and open ARC standards.
- Click ARC production is covered by article 11B certification.



Product Code:
CARC51

Available in Sizes:
S - 6XL

Available in Colours:



Orange
CARC51OR



Anti Static



Arc Flash Protection



Fire Retardant



Hi Visibility



Product Code:
CARC3

Available in Sizes:
S - 6XL

Available in Colours:



Navy Blue
CARC3N



Anti Static



Arc Flash Protection



Fire Retardant

ARC COMPLIANT LONG SLEEVE T-SHIRT

- Flame Retardant, Anti-Static, ARC Long sleeved T- Shirt (under garment).
- 210gsm 60/40 Modacrylic/ cotton with anti static.
- Inherently flame retardant fabric.
- FR properties will not diminish with repeated laundering
- Soft comfortable fabric with contrast FR sewing thread

EN ISO 13688: 2013
EN 1149-3: 2008
EN 1149-5: 2015
EN ISO 11612: 2015 (A1 B1 C1)
EN ISO 14116: 2015 (3/5H/40)

IEC 61482-2-2009
EN 61482-1-2-2007 (Class 1 = 4 kA) - Box Arc testing
EN 61482 - 1 - 1 : 2009 (EBT50 = 5.9 cAL/cm2) Open Arc testing

- Each garment style is independantly tested to both box and open ARC standards.
- Click ARC production is covered by article 11B certification.



ARC COMPLIANT LONG JOHN

- Flame Retardant, Anti-Static, ARC Long Johns (under garment).
- 210gsm 60/40 Modacrylic/ cotton with anti static.
- Inherently flame retardant fabric.
- FR properties will not diminish with repeated laundering
- Soft comfortable fabric with contrast FR sewing thread

EN ISO 13688: 2013
EN 1149-3: 2008
EN 1149-5: 2015
EN ISO 11612: 2015 (A1 B1 C1)
EN ISO 14116: 2015 (3/5H/40)

IEC 61482-2-2009
EN 61482-1-2-2007 (Class 1 = 4 kA) - Box Arc testing
EN 61482 - 1 - 1 : 2009 (EBT50 = 5.9 cAL/cm2) Open Arc testing

- Each garment is independantly tested to both box and open ARC standards.
- Click ARC production is covered by article 11B certification.



Product Code:
CARC22

Available in Sizes:
S-4XL

Available in Colours:



As Shown
CARC22



Product Code:
CARC24

Available in Sizes:
S-4XL

Available in Colours:



As Shown
CARC24

ARC FLASH TROUSERS

- Fire retardent, Anti-static, ARC Flash cargo style trousers.
- 300gsm 60/40 Modacrylic/cotton blend.
- Inherently flame retardent.
- Flame retardent qualities will not diminish during life of garment.
- Triple stitch construction.
- 7 belt loop part elastic waisband, double button closure.
- 2 hip pockets.
- Rear patch pocket with velcro closure flap.
- Large bellows pocket to each leg with velcro closure flap.
- Right leg mobile phone pocket with velcro closure flap.
- All pocket flaps with Retro-reflective tape feature.
- Internal knee pad pouches.
- Large qualifying icons on left leg pocket.

Leg length:
Small (S) - 29"
Regular - 31"
Tall (T) - 33"

EN ISO 13688:2013 - General requirements for protective clothing
EN 1149-3:2004 - Anti Static - Test methods for measurements of charge decay
EN 1149-5:2008 - Anti Static - Material performance and design requirements
EN ISO 11611:2007 (Class 1 A1 A2) - Protective clothing for use in welding
EN ISO 11612:2008 (A1 A2 B1 C1) - Protection against heat and flame

ARC FLASH

IEC 61482-2:2009 - Performance requirements and design requirements
EN 61482-1-2:2007 (Class 1 = 4kA) - Box Arc testing
EN 61482-1-1:2009 (ATPV = 10.8 Cal/cm2) - Open Arc testing

- Each garment style is independantly tested to both box and open ARC standards.
- Click ARC production is covered by article 11B certification.



ARC FLASH HI VIZ TROUSERS

- Fire Retardant, Hi Vis, Anti-static, ARC Flash cargo style trousers.
- 300gsm 60/40 Modacrylic/cotton blend.
- Triple stitch construction.
- 7 belt loop part elastic waisband, double button closure.
- 2 hip pockets.
- Rear patch pocket with velcro closure flap.
- Large bellows pocket to each leg with velcro closure flap.
- Right leg mobile phone pocket with velcro closure flap.
- All pocket flaps with Retro-reflective tape feature.
- Internal knee pad pouches.
- Large qualifying icons on left leg pocket.

• EN ISO 13688:2013 - General requirements for protective clothing
• EN ISO 20471:2013 Class 2 - Test method for high visibility
• EN 1149-3:2004 - Anti Static - Test methods for measurements of charge decay
• EN 1149-5:2008 - Anti Static - Material performance and design requirements
• EN ISO 11611:2007 (Class 1 A1 A2) - Protective clothing for use in welding
• EN ISO 11612:2008 (A1 A2 B1 C1) - Protection against heat and flame

ARC FLASH

IEC 61482-2:2009 - Performance requirements and design requirements
EN 61482-1-2:2007 (Class 1 = 4kA) - Box Arc testing
EN 61482-1-1:2009 (ATPV = 10.8 Cal/cm2) - Open Arc testing

- Each garment style is independantly tested to both box and open ARC standards.
- Click ARC production is covered by article 11B certification.



Product Code:
CARC4

Available in Sizes:
28" - 50" (Short & Tall Leg
Available)

Available in Colours:



Navy Blue
CARC4N



Anti Static



Arc Flash Protection



Fire Retardant



Protection for Welding and
Allied Processes



Product Code:
CARC5

Available in Sizes:
30" - 50" (Tall Leg
Available)

Available in Colours:



Saturn Yellow / Navy
CARC5SYN



Anti Static



Arc Flash Protection



Fire Retardant



Hi Visibility



Protection for Welding and
Allied Processes

ARC FLASH GO/RT TROUSERS

- Fire Retardant, Hi Vis, Anti-static, ARC Flash, orange cargo style trousers.
- GO/RT 3279 issue 8 2013 for use on or around railway lines.
- 310gsm 40% Modacrylic, 24% FR Viscose, 20% Polyester, 10% Cotton, 4% Aramid, 2% Anti-static Fibre.
- 7 belt loop part elastic waistband, double button closure.
- 2 hip pockets.
- Rear patch pocket with velcro closure flap.
- Large bellows pocket to each leg with velcro closure flap.
- Right leg mobile phone pocket with velcro closure flap.
- All pocket flaps with Retro-reflective tape feature.
- Internal knee pad pouches.
- Large qualifying icons on left leg pocket.
- Adjustable leg bellows.
- Tall leg sizes available.

- EN ISO 13688:2013 - General requirements for protective clothing
- EN ISO 20471:2013 Class 2 - Test method for high visibility - GORT 3279 Issue 8
- EN 1149-3:2004 - Anti Static - Test methods for measurements of charge decay
- EN 1149-5:2008 - Anti Static - Material performance and design requirements
- EN ISO 11611:2015 (Class 1 A1 A2) - Protective clothing for use in welding
- EN ISO 11612:2015 (A1 A2 B1 C1) - Protection against heat and flame

ARC FLASH

IEC 61482-2:2009 - Performance requirements and design requirements

EN 61482-1-2:2007 (Class 1 = 4kA) - Box Arc testing

EN 61482-1-1:2009 (ATPV = 16 Cal/cm2) - Open Arc testing

- Each garment style is independently tested to both box and open ARC standards.
- Click ARC production is covered by article 11B certification.



Product Code:
CARC52OR

Available in Sizes:
30 - 50 (Tall Leg Available)

Available in Colours:

Orange
CARC52OR



Anti Static



Arc Flash Protection



Fire Retardant



Hi Visibility



Protection for Welding and
Allied Processes



TRADE MARKED AND COPYRIGHT© PROTECTED. ALL RIGHTS RESERVED 2005

www.clickalogue.com

All Click Logos, 'Clickalogue', 'Click'

Trademarked to: P.O. Box 13636, West Bromwich, B70 1BQ



Your local **CLICK** **ARC** Distributor

HEALTH & SAFETY ADVISORY SERVICE
5 CRASTER DRIVE
ARNOLD
NOTTINGHAM
NG5 8SL

t: 01159523096
e: hsasppe@gmail.com